

# ALL THREAD ROD AND POINT EXTENSION ROD

ALL ITEMS



## ALL THREAD ROD

All thread rod with standard N.C. threads. Available in lengths up to 144". Standard sizes 12", 18", 24", 36".

### Copper

**Cat. No. 220** – 3/8" dia. 0.57 oz./in.

**Cat. No. 221** – 1/2" dia. 1 oz./in.

**Cat. No. 222** – 5/8" dia. 1.6 oz./in.

### Aluminum

**Cat. No. A221** – 1/2" dia. 0.3 oz./in.

**Cat. No. A222** – 5/8" dia. 0.48 oz./in.

### Stainless Steel

**Cat. No. 220SS** – 3/8" dia. 0.5 oz./in.

**Cat. No. 221SS** – 1/2" dia. 0.89 oz./in.



## POINT EXTENSION ROD

Solid copper or aluminum rod for extending length of points – standard N.C. thread both ends – available in lengths to 144". May also be substituted for stranded cable to prevent mechanical damage or to bridge open spaces.

Specify exact length required, such as Cat. No. 212 (1/2" x 48").

### Copper

**Cat. No. 212** – 1/2" dia. 1 oz./in.

**Cat. No. 213** – 3/8" dia. 0.57 oz./in.

**Cat. No. 214** – 5/8" dia. 1.6 oz./in.

### Aluminum

**Cat. No. A212** – 1/2" dia. 0.3 oz./in.

**Cat. No. A214** – 5/8" dia. 0.48 oz./in.



## SAFETY BALLS

Machined brass or aluminum safety tip, 1-1/2" diameter, with internal threads - to be used on copper or aluminum extension rods in place of standard sharp points where safety to workers or pedestrians is a concern.


**Cat. No. 110F** – Copper - 2.2 oz.

**Cat. No. A110F** – Aluminum - 0.8 oz.


**Cat. No. 110** – Copper - 7.7 oz.

**Cat. No. A110** – Aluminum - 2.4 oz.


Specify diameter of threads – 3/8", 1/2" or 5/8".




NO. 110



Typical use on midroof point



NO. 110F



NO. 110C

## SAFETY SLEEVE WITH SET SCREW

**Cat. No. 110C** – Copper - 4 oz.

**Cat. No. A110C** – Aluminum - 1.5 oz.

Specify diameter of point.

# ROBBINS LIGHTNING, INC.

124 EAST SECOND STREET PHONE (660) 582-3156 FAX (660) 582-3039 P.O. BOX 440 MARYVILLE, MISSOURI 64468-0440

